

Interior Horizontal Slider> Specification

Below is the general specifications for Maine Glass horizontal sliderinterior insulating window
Horizontal Slider Aluminum Interior Insulating Windows

I. General

- A. Work - Included - Provide all laor, material and equipment necessary to manufacture and deliver fixed interior insulating window designed compatible with Between-the-Glass blinds and components as specified.
- B. Product Overview - Removable fixed panel windows. Trackwork (described below) and blind (if applicable) are installed first, pre-glazed window in sash (described below) is then inserted up and into the opening. Window seals to trackwork with a wool pile compression seal at top and bottom (sill and header).

II. Description

- A. Standard windows shall be 3/16" glass. Other glazing options are available to meet the requirements of the project.
- B. Window shall be glazed into aluminum sash rail with mitered and screwed corners.
- C. Refer to Horizontal Slider Detail Drawing.
- D. Color is to be specified by customer.

III. Submittals

- A. Detailed written installation instructions and drawings shall be included upon request.
- B. Samples of material may be furnished upon request, with a cost to the customer.
- C. Independent product performance test results shall be furnished upon request.

IV. Warranty

- A. Five year warranty on the material. Five year warranty on all components that are defective in material or workmanship for five years from the delivery date. Under no circumstances does this warranty cover glass broken after the delivery has been accepted, or any material that is damaged during installation.

V. Products/Materials

- A. Refer to Horizontal Slider Detail Drawing.

VI. Execution

- A. Final inspection shall be by the manufacturer before shipping.

B. Unloading of Delivery Truck and Installation shall be the responsibility of others.

*Continued efforts in product improvement may change product specifications.